



TECHNICAL DATASHEET

HEALTHCARE TAPWARE

Thermostatic shower mixer, special thermal shock, with hydrotherapy kit - 75107



Benefits of the product

- French Norm (NF) compliant thermostatic cartridge
- Dual flow rate
- Temperature limiter locked at 38°C and 41°C (dual temperature limiter)
- Secure release system for thermal shock (without changing knob)
- Anti-stagnation connector to drain the hose

Description

150mm span thermostatic wall-mount shower mixer Dual flow control knob and a special heat shock knob locked at 38 °C and 41°C with a secure release system for thermal shock without changing knob and accessible only by technical services. Hot and cold water supplies equipped with back-flow valves, shower outlet M'1 / 2. ½ turn ceramic head for flow control and NF Thermostatic cartridge for adjusting the temperature. Body and knobs in polished chrome-plated brass. Supplied with off-centre fittings M1 / 2 with chrome rosette cover plates and filter seals; 5-spray shower; metal plastic hose L 0.85m; wall bracket, 5-positions and anti-stagnation fitting. (hose purge. 3-year warranty for the thermostatic cartridge and 10 years for the rest of the fittings. Sanifirst brand thermostatic shower mixer, 150mm span, REF: 75107 or approved equivalent.





TECHNICAL DATASHEET

Additional Information

Product reference	75107
Previous reference	FL3730CT HYG
Brand	Sanifirst
Warranty	10 years against manufacturing defects / 3 years for the thermostatic cartridge
Special feature 1	1/2 turn ceramic head
Special feature 2	Shower
Clip-on spout	No
Lever	Brass knobs
Connection	LN G'3 / 4 comes with rosettes and off-centre fittings M G'1 / 2 - M G'3 / 4
Minimum pressure	1 bar
Recommended pressure	3 bar - avoid pressure differences of more than 1 bar between the hot and cold water supplies
Maximum pressure	5 bar
Cartridge	Thermostatic
Coating	Nickel > 10 microns - Chrome > 0.3 microns