




## **TECHNICAL DATASHEET**

### **HEALTHCARE TAPWARE**

Thermostatic bath shower mixer - dual hole - baby changing sink - Mastermix Mini - 75111





#### Benefits of the product

- Ergonomic lever handle: easy grip
- Smooth interior removable spout: easy cleaning and disinfection, limits the formation of biofilm.
- Star shaped flow straightener: Limits the water spray, no water retention.

#### **Description**

Thermostatic shower-bath mixer MASTERMIX design for baby changing sink with extractable shower, 2-hole.

Unique patented system avoiding communication between hot and cold water supplies eliminating back-flow valves on mixer supplies using a ceramic cartridge and a thermostatic cartridge NF EN 111.

Temperature knob locked at 38  $^{\circ}$  C. Secured release for thermal shock accessible only by technical services without need to remove knob. SPEX hose, M8X1, LN G'3 / 8 L 350mm; 10-year warranty -

Thermostatic cartridge 3-year warranty; REF: 75111 or approved equivalent.





# **TECHNICAL DATASHEET**

#### **Additional Information**

| Product reference     | 75111   |
|-----------------------|---|
| Previous reference    | FL3923CT  |
| Brand                 | Sanifirst   |
| Warranty              | 10 years against manufacturing defects / 3 years for the thermostatic cartridge               |
| Special feature 1     | Shower head   |
| Special feature 2     | Tabletop  |
| Special feature 3     | Swivel spout  |
| Special feature 4     | Mixer   |
| Height to nozzle (mm) | 232   |
| Projection (mm)       | 190   |
| Direction of lever    | Vertical  |
| Clip-on spout         | No  |
| Drainage              | Without drainage  |
| Flow straightener     | Star shaped flow straightener, M24 x 1  |
| Lever                 | Brass knobs   |
| Connection            | SPEX hoses 350 mm - M8 X 1 - LN G'3 / 8   |
| Minimum pressure      | 1 bar   |
| Recommended pressure  | 3 bar - avoid pressure differences of more than 1 bar between the hot and cold water supplies |
| Maximum pressure      | 5 bar   |
| Cartridge             | NF ceramic cartridge and thermostatic cartridge   |
| Coating               | Nickel > 10 microns - Chrome > 0.3 microns  |
| Thermal shock         | Yes   |