



### HEALTHCARE TAPWARE

#### Thermostatic shower mixer, thermal shock - Mastermix - with hydrotherapy kit - 75113



#### Benefits of the product

- MASTERMIX PATENTED TECHNOLOGY
- No communication between hot and cold water
- No back-flow valve needed
- Cold body: safety insulation
- Temperature and flow controls easily identifiable
- Temperature maintenance and anti-scald insulation
- Quick and easy maintenance
- Swivel and removable upward cast spout

#### Description

Thermostatic shower mixer MASTERMIX design equipped with ergonomic downward flow control handle.

Temperature knob locked at 38 ° C (Secured release for thermal shock accessible only by technical services without need to remove knob.)

150mm span, off centre M 1/2 fittings with chrome cover plates and filter seals. Shower output M'1 / 2 downward with integrated back-flow valve. Adjustable flow rate between 5 and 14l/min, adjustable temperature from 18 to 38 ° C. Comes with 1-spray shower head, 0.85 hose, 5-position wall-mount, purge hose.

Unique patented system avoiding communication between hot and cold water supplies eliminating back-flow valves on mixer supplies using a ceramic cartridge and a thermostatic cartridge NF EN 111.

3-year warranty for the thermostatic cartridge and 10-year warranty for the rest of the fittings. PART NO.: 75113, MASTERMIX design, Sanifirst brand or approved equivalent.



## TECHNICAL DATASHEET

### Additional Information

<b>Product reference</b>	75113
<b>Previous reference</b>	FL3930CT HYG
<b>Brand</b>	Sanifirst
<b>Warranty</b>	10 years against any manufacturing defect and 3 years for the thermostatic cartridge
<b>Special feature 2</b>	Shower
<b>Special feature 3</b>	Wall-mounted
<b>Special feature 4</b>	Mixer
<b>Clip-on spout</b>	No
<b>Lever</b>	Downward opening / closing handle and T ° C thermal shock brass knob
<b>Connection</b>	LN G'3 / 4 comes with rosettes and off-centre fittings M G'1 / 2 - M G'3 / 4
<b>Flow rate</b>	Estimate: adjustable between 5 and 14l/min
<b>Minimum pressure</b>	1 bar
<b>Recommended pressure</b>	3 bar - avoid pressure differences of more than 1 bar between the hot and cold water supplies
<b>Maximum pressure</b>	5 bar
<b>Cartridge</b>	NF ceramic cartridge and thermostatic cartridge
<b>Coating</b>	Nickel > 10 microns - Chrome > 0.3 microns
<b>Thermal shock</b>	Yes