




TECHNICAL DATASHEET

HEALTHCARE TAPWARE

Hospital spout, wall mount, fixed upward - 75220





Benefits of the product

- Height to spout and projection comfortable for easy washing
- Suitable for installation of a terminal filter.
- Star shaped flow straightener: Limits the water spray, no water retention.
- Chlorine and thermal shock resistant.

Description

Monofluid hospital wall-mount gooseneck spout, for use with remote control (foot, femoral type or remote control mixer). Smooth tube spout, fixed, removable, L 200 mm. Height to nozzle 170mm suitable for end filtration. Tapware with star-shaped flow straightener reducing scaling, eliminating water retention and impurities; withstands thermal and chlorine shocks Smooth body and polished chrome-plated brass spout. M1/2 connection 10 year warranty. Chlorine and thermal shock resistant. Sanifirst brand hospital upward gooseneck spout, fixed and removable smooth tube REF: 75220 or approved equivalent.





TECHNICAL DATASHEET

Additional Information

| Product reference | 75220 |
|-----------------------------|--|
| Previous reference | FL9400MA |
| Brand | Sanifirst |
| Warranty | 10 years against manufacturing defects |
| Special feature 1 | Fixed spout |
| Special feature 3 | Wall-mounted |
| Height to nozzle (mm) | 170 |
| Lenght of spout (mm) | 200 |
| Projection (mm) | 230 |
| Clip-on spout | No |
| Flow straightener | Star shaped flow straightener, M24 x 1 |
| Connection | M G'1/2 |
| Minimum pressure | 1 bar |
| Recommended pressure | 3 bar |
| Maximum pressure | 5 bar |
| Lenght of threaded rod (mm) | 56 |
| Max tightening | 20 |
| Coating | Nickel> 10 microns - Chrome> 0.3 microns |