




# **TECHNICAL DATASHEET**

### **HEALTHCARE TAPWARE**

## Hospital gooseneck spout, wall mount, fixed upward and removable - 75222









### Benefits of the product

- Modul'Mix Range: modularity of parts and adaptability to actual needs
- Retrofitable and customisable
- Ergonomic: easy to use elbow handle (for patients and technical staff)
- Hand hygiene: avoiding manual contact
- Multifunction cartridge: 7-setting temperature limit stop, dual flow and flow setting.
- Smooth interior tube, fixed or swivel, removable spout: easy cleaning and disinfection, limits the formation of biofilm.
- Quick and easy maintenance
- Quick release base

#### **Description**

Monofluid hospital wall-mount gooseneck spout, for use with remote control (foot, femoral type or remote control mixer). Smooth tube spout, fixed, removable, L 150 mm. Height to nozzle 117mm suitable for end filtration. Tapware with star-shaped flow straightener reducing scaling, eliminating water retention and impurities; withstands thermal and chlorine shocks Smooth body and polished chrome-plated brass spout. M1/2 connection 10 year warranty. Chlorine and thermal shock resistant. Sanifirst brand hospital upward gooseneck spout, fixed and removable smooth tube REF: 75222 or approved equivalent.





# **TECHNICAL DATASHEET**

#### **Additional Information**

Product reference	75222
Previous reference	FL9404MA
Brand	Sanifirst
Warranty	10 years against manufacturing defects
Special feature 1	Fixed spout
Special feature 2	Removable spout
Height to nozzle (mm)	117
Lenght of spout (mm)	150
Projection (mm)	180
Clip-on spout	No
Connection	M G'1/2
Minimum pressure	1 bar
Recommended pressure	3 bar
Maximum pressure	5 bar
Lenght of threaded rod (mm)	56
Max tightening	20
Coating	Nickel > 10 microns - Chrome > 0.3 microns