




TECHNICAL DATASHEET

HEALTHCARE TAPWARE

Hospital spout, wall mount, fixed downward - 75229





Benefits of the product

- Smooth tube downward spout: easy cleaning and disinfection, limits the formation of biofilm.
- Suitable for installation of a terminal filter.
- Star shaped flow straightener: Limits the water spray, no water retention.
- Chlorine and thermal shock resistant.

Description

Monofluid hospital wall-mount gooseneck spout, for use with remote control (foot, femoral type or remote control mixer). Smooth tube spout, fixed, removable, L 200 mm. Height to nozzle 100mm suitable for end filtration. Tapware with star-shaped flow straightener reducing scaling, eliminating water retention and impurities; withstands thermal and chlorine shocks Smooth body and polished chrome-plated brass spout. M1/2 spout connection. 10-year warranty. Chlorine and thermal shock resistant. Sanifirst brand hospital upward gooseneck spout, fixed and removable smooth tube REF: 75229 or approved equivalent.





TECHNICAL DATASHEET

Additional Information

Product reference	75229
Previous reference	FL9600MA
Brand	Sanifirst
Warranty	10 years against manufacturing defects
Special feature 1	Fixed spout
Special feature 3	Wall-mounted
Height to nozzle (mm)	100
Lenght of spout (mm)	200
Projection (mm)	230
Clip-on spout	No
Flow straightener	Star shaped flow straightener, M24 x 1
Connection	M G'1/2
Minimum pressure	1 bar
Recommended pressure	3 bar
Maximum pressure	5 bar
Lenght of threaded rod (mm)	56
Max tightening	20
Coating	Nickel> 10 microns - Chrome> 0.3 microns