



### HEALTHCARE TAPWARE

## Thermostatic sink mixer, upward handle and downward swivel spout - Mastermix - 75310



### Benefits of the product

- Ergonomic: easy to use elbow handle (for patients and technical staff)
- Smooth interior tube removable tube: easy cleaning and disinfection, limits the formation of biofilm.
- Multifunction cartridge: 7-setting temperature limit stop, dual flow and settings from 2l to 13.8l/min.
- Star shaped flow straightener: Limits the water spray, no water retention.

### Description



Thermostatic sink mixer MASTERMIX design equipped with ergonomic upward flow control handle.

Temperature knob with stop at 38°, releasable to 45°C

150mm span, off centre M 1/2 fittings with chrome cover plates and filter seals. Downward spout L 200mm. Flow adjustable between 5 and 14l/min

Unique patented system avoiding communication between hot and cold water supplies eliminating back-flow valves on mixer supplies using a ceramic cartridge and a thermostatic cartridge NF EN 111.

3-year warranty for the thermostatic cartridge and 10-year warranty for the rest of the fittings. PART NO.: 75310, MASTERMIX design, Sanifirst brand or approved equivalent.





## TECHNICAL DATASHEET

### Additional Information

<b>Product reference</b>	75310
<b>Previous reference</b>	SF3936AA
<b>Brand</b>	Sanifirst
<b>Warranty</b>	10 years against manufacturing defects / 3 years for the thermostatic cartridge
<b>Special feature 1</b>	Sink
<b>Special feature 2</b>	Underneath spout
<b>Special feature 3</b>	Removable spout
<b>Height to nozzle (mm)</b>	130
<b>Length of spout (mm)</b>	200
<b>Projection (mm)</b>	285
<b>Clip-on spout</b>	No
<b>Flow straightener</b>	Aerator, F24 X 1
<b>Lever</b>	Upward opening / closing handle and T ° C brass knob
<b>Connection</b>	LN G'3 / 4 comes with rosettes and off-centre fittings M G'1 / 2 - M G'3 / 4
<b>Flow rate</b>	Estimate: adjustable between 5 and 14l/min
<b>Minimum pressure</b>	1 bar
<b>Recommended pressure</b>	3 bar - avoid pressure differences of more than 1 bar between the hot and cold water supplies
<b>Maximum pressure</b>	5 bar
<b>Cartridge</b>	One thermostat and one ceramic
<b>Coating</b>	Nickel > 10 microns - Chrome > 0.3 microns
<b>Thermal shock</b>	No