





HEALTHCARE TAPWARE

Thermostatic sink mixer with downward spout, downward handle, thermal shock - Mastermix - 75317



Description

Thermostatic sink mixer, MASTERMIX design, 150mm span, downward tube spout, projection 200mm, fitted with a downward ergonomic flow opening / closing handle, very different T°C control for easy identification, a thermal shock control locked at 38 ° C with release system for thermal shock without need for removable accessible only by technical services. Ceramic cartridge, diam 47; thermostatic cartridge NF EN 1111. Adjustable flow rate between 5 and 14l/min, adjustable temperature from 18 to 38 ° C. Off centre M 1/2 fittings with chrome cover plates and filter seals. 3-year warranty for the thermostatic cartridge and 10-year warranty for the rest of the fittings. Unique patented system avoiding communication between hot and cold water supplies eliminating back-flow valves on mixer supplies. PART NO.: 75317 - Sanifirst brand or approved equivalent.





TECHNICAL DATASHEET

Additional Information

Product reference	75317
Previous reference	FL3937CT
Brand	Sanifirst
Warranty	10 years against manufacturing defects / 3 years for the thermostatic cartridge
Special feature 1	Sink
Special feature 2	Underneath spout
Special feature 3	Swivel spout
Special feature 4	Thermostatic mixer
Height to nozzle (mm)	130
Length of spout (mm)	200
Projection (mm)	285
Clip-on spout	No
Flow straightener	Star shaped flow straightener, M24 x 1
Connection	LN G'3 / 4 comes with rosettes and off-centre fittings M G'1 / 2 - M G'3 / 4
Flow rate	Estimate: adjustable between 5 and 14l/min
Minimum pressure	1 bar
Recommended pressure	3 bar
Maximum pressure	5 bar
Cartridge	NF ceramic cartridge and thermostatic cartridge
Coating	Nickel > 10 microns - Chrome > 0.3 microns