



TECHNICAL DATASHEET

HEALTHCARE TAPWARE

Single hole washbasin mixer tap with fixed cast spout without drainage - 75613



Benefits of the product

- Perfectly adapted to all bathrooms.
- Openwork control: easier to grip.
- Multifunctional cartridge: temperature limit stop with 7 adjustment positions, double flow (hard point at 50% opening).
- Flow between 4 and 6L / min at 3 bar in accordance with the French norm standard "Medical"; possible flow modification, in case of disassembly of the limiters, by adjusting screw between 4 and 20L / min.
- Water savings, safety of use and controlled water consumption.

Description

Single-hole deck-mounted hand-basin mixer tap without drainage, with open-work control. Fixed cast spout Len 119mm. Spout height 53.5mm. Ø 40 multi-function ceramic cartridge: 7-setting temperature limit stop, dual flow (hard point at 50% opening). Flow between 4 and 6L / min at 3 bar - in accordance with the NF standard "medical environment"; possible flow modification, in case of disassembly of the limiters, by adjusting screw between 4 and 20L / min.. Tapware fitted with star-shaped aerator as standard. Body, spout and control component in polished chrome-plated brass. Hoses with SPEX sheath braided stainless steel M12X1, EP G'3/8, Len 370mm. Basket filter seals mounted on the hoses limiting fouling. Fixture strengthened using an M8 rod. 10 year guarantee. Sanifirst brand type single hole washbasin mixer tap fixed with cast spout REF: 75613 or approved equivalent.





TECHNICAL DATASHEET

Additional Information

| Product reference | 75613 |
|-----------------------|--|
| Previous reference | NC |
| Brand | Sanifirst |
| Warranty | 10 years against manufacturing defects |
| Special feature 1 | Fixed spout |
| Height to nozzle (mm) | 53 |
| Projection (mm) | 119 |
| Clip-on spout | No |
| Drainage | Without drainage |
| Flow straightener | Star-shaped flow straightener, M24X1 |
| Lever | Openwork lever |
| Connection | SPEX hoses 350 mm - M12 X 1 - LN G'3 / 8 with basket filter seals and flow rate limiters |
| Minimum pressure | 1 bar |
| Recommended pressure | 3 bar |
| Maximum pressure | 5 bar |
| Cartridge | 75312 Ø 40mm, dual flow, flow limiter and temperature limiter |
| Coating | Nickel> 10 microns - Chrome> 0.3 microns |