





TECHNICAL DATASHEET

HEALTHCARE TAPWARE

Sink one-hole mixer - Energy savings - with drainage - 75697







Benefits of the product

- Opening on cold water: avoid to use hot water at the opening (energy savings)
- Spout height and projections fitted to the toilette at the washbasin
- Fits perfectly to all kind of bathroom
- Multifunctional cartridge: temperature limit stop with 7 adjustment positions, double flow (hard point at 50% opening).
- Flow between 4 and 6L / min at 3 bar in accordance with the French norm standard "Medical"; possible flow modification, in case of disassembly of the limiters, by adjusting screw between 4 and 20L / min.
- Water savings and water consumption control

Description

Sink one-hole mixer tap with "clic-clac" drainage - deck-mounted model with thin lever. Fixed cast spout with 170.5 mm projection. Spout height: 252 mm. Ø 35 mm ceramic cartridge with energy savings: opening on cold water. Flow between 4 and 6L / min at 3 bar - in accordance with the NF standard "medical environment"; possible flow modification, in case of disassembly of the limiters, by adjusting screw between 4 and 20L / min. Tapware fitted as standard star-shaped flow straightener. Body, spout and controls in polished chrome plated brass. SPEX stainless steel braided hoses, M10X1, EP G'3/8, Lg 480mm. Basket filter seals mounted on the hoses limiting fouling. Reinforced fixation by a stainless steel rod M8. 10 year warranty. Sanifirst brand single hole washbasin mixer, fixed cast spout REF: 75697 or approved equivalent.





TECHNICAL DATASHEET

Additional Information

Product reference	75697
Previous reference	NC
Brand	Sanifirst
Warranty	10 years against manufacturing defect
Height to nozzle (mm)	252
Projection (mm)	170
Height of lever (mm)	310
Clip-on spout	No
Flow straightener	Flow rate straightener, M24X1
Lever	Wire lever
Connection	M10X1 hose, EP G'3/8 Lg 480 mm SPEX with basket filter seals and flow rate limiters
Minimum pressure	1 bar
Recommended pressure	3 bar
Maximum pressure	5 bar
Cartridge	75641, diamètre 35 mm, type C3 - économies d'énergie