





## **TECHNICAL DATASHEET**

### **HEALTHCARE TAPWARE**

## Sink one-hole mixer - Energy savings - without drainage - 75698







#### Benefits of the product

- Opening on cold water: avoid to use hot water at the opening (energy savings)
- Spout height and projections fitted to the toilette at the washbasin
- Fits perfectly to all kind of bathroom
- Flow between 4 and 6L / min at 3 bar in accordance with the French norm standard "Medical"; possible flow modification, in case of disassembly of the limiters, by adjusting screw between 4 and 20L / min.
- Water savings and water consumption control

#### Description

One-hole sink mixer tap without "clic-clac" drainage - deck-mounted model with thin lever. Fixed cast spout with 170.5 mm projection. Spout height: 252 mm. Ø 35 mm ceramic cartridge with energy savings: opening on cold water. Flow between 4 and 6L / min at 3 bar - in accordance with the NF standard "medical environment"; possible flow modification, in case of disassembly of the limiters, by adjusting screw between 4 and 20L / min. Cartridge fitted with a mechanical temperature limiting stop allowing adjustment in 5 positions. Tapware fitted as standard star-shaped flow straightener. Body, spout and controls in polished chrome plated brass. SPEX stainless steel braided hoses, M10X1, EP G'3/8, Lg 480mm. Basket filter seals mounted on the hoses limiting fouling. Reinforced fixation by a stainless steel rod M8. 10 year warranty. Sanifirst brand single hole washbasin mixer, fixed cast spout REF: 75698 or approved equivalent.





# **TECHNICAL DATASHEET**

#### **Additional Information**

Product reference	75698
Previous reference	NC
Brand	Sanifirst
Warranty	10 years against manufacturing defect
Height to nozzle (mm)	252
Projection (mm)	170
Height of lever (mm)	310
Clip-on spout	No
Drainage	Without drainage
Flow straightener	Star-shaped flow straightener, M24X1
Lever	Wire lever
Connection	M10X1 hose, EP G'3/8 Lg 480 mm SPEX with basket filter seals and flow rate limiters
Minimum pressure	1 bar
Recommended pressure	3 bar
Maximum pressure	5 bar
Cartridge	75641, diamètre 35 mm, type C3 économies d'énergie