



TECHNICAL DATASHEET

LABORATORY TAPWARE

Gooseneck on backrest with swivel spout - 76019





Benefits of the product

Coating: black Rilsan

Description

Gooseneck for backsplash with smooth swivel removable spout, for drinking water. Thread connection M G'1/2, Ø 10mm removable serrated tip, 200mm projection. Base and flanged washer according to colour codes of the European standard NF EN 13792. Maximum tightening 55mm. Brass body and nozzle with black Nylolac coating (stronger than simple Epoxy finish). Unique and patented reinforced mounting kit, the serrated tips are designed for a steel claw washer thereby preventing rotation of the tapware. 5 year warranty. First Labo brand gooseneck for backsplash with smooth swivel removable spout REF: 76019 or approved equivalent.





TECHNICAL DATASHEET

Additional Information

Product reference	76019
Previous reference	H9025PT
Brand	FirstLabo
Warranty	5 years against manufacturing defect
Special feature 1	Remotely controlled tapware/ laboratory fume hood
Special feature 2	Backsplash
Special feature 3	Swivel spout
Nozzle 1	Removable connector Ø10 mm
Base color EN	Green
Base washer color EN	Blue
Additional information	Installation possible for fume cabinet
Height to nozzle (mm)	180
Lenght of spout (mm)	150
Projection (mm)	200
Connection	Threaded connection M G'1 / 2
Adjustable flow rate	No
Dual flow rate	No
Minimum pressure	1 bar
Recommended pressure	3 bar
Maximum pressure	5 bar
Blocking temperature	No
Lenght of threaded rod (mm)	102
Max tightening	55
Packing	1