



### LABORATORY TAPWARE

#### Gooseneck on backrest with swivel spout - 76023



#### Benefits of the product

Coating: black Rilsan

#### Description

Gooseneck for backsplash with smooth swivel removable spout, for drinking water. Thread connection M G'1/2,  $\varnothing$  10mm removable serrated tip, 250mm projection. Base and flanged washer according to colour codes of the European standard NF EN 13792. Maximum tightening 55mm. Brass body and nozzle with black Nylolac coating (stronger than simple Epoxy finish). Unique and patented reinforced mounting kit, the serrated tips are designed for a steel claw washer thereby preventing rotation of the tapware. 5 year warranty. First Labo brand gooseneck for backsplash with smooth swivel removable spout REF: 76023 or approved equivalent.



## TECHNICAL DATASHEET

### Additional Information

<b>Product reference</b>	76023
<b>Previous reference</b>	H9125PT
<b>Brand</b>	FirstLabo
<b>Warranty</b>	5 years against manufacturing defect
<b>Special feature 1</b>	Remotely controlled tapware/ laboratory fume hood
<b>Special feature 2</b>	Backsplash
<b>Special feature 3</b>	Swivel spout
<b>Nozzle 1</b>	Removable connector Ø10 mm
<b>Base color EN</b>	Green
<b>Base washer color EN</b>	Blue
<b>Additional information</b>	Installation possible for fume cabinet
<b>Height to nozzle (mm)</b>	180
<b>Length of spout (mm)</b>	200
<b>Projection (mm)</b>	250
<b>Connection</b>	Threaded connection M G'1 / 2
<b>Adjustable flow rate</b>	No
<b>Dual flow rate</b>	No
<b>Minimum pressure</b>	1 bar
<b>Recommended pressure</b>	3 bar
<b>Maximum pressure</b>	5 bar
<b>Blocking temperature</b>	No
<b>Length of threaded rod (mm)</b>	102
<b>Max tightening</b>	55
<b>Packing</b>	1