




TECHNICAL DATASHEET

LABORATORY TAPWARE

Candlestick type table top twin tap with fixed spout - 76030







Benefits of the product

Coating: black Rilsan

Description

Tamper proof dual lab tap (double thickness tube), National Education standard, smooth fixed spout for drinking water. Threaded connection M G'1 / 2, fixed serrated tip Ø 6mm and removable serrated tip Ø 10mm, 150mm projection. Polypropylene brace and flanged washer according to colour codes of the European standard NF EN 13792. Maximum tightening 65mm. Brass body and nozzle with black Nylolac coating (stronger than simple Epoxy finish). Unique and patented reinforced mounting kit, the serrated tips are designed for a steel claw washer thereby preventing rotation of the tapware. 5 year warranty. First Labo brand double deck-mount lab tap with smooth fixed spout REF: 76030 or approved equivalent.





TECHNICAL DATASHEET

Additional Information

| Product reference | 76030 |
|-----------------------------|--------------------------------------|
| Previous reference | H9077PT |
| Brand | FirstLabo |
| Warranty | 5 years against manufacturing defect |
| Special feature 1 | Candlestick |
| Special feature 2 | Tabletop |
| Special feature 3 | Fixed spout |
| Nozzle 1 | Fixed connector Ø6 mm |
| Nozzle 2 | Removable connector Ø10 mm |
| Base washer color EN | Blue |
| Insert color EN | Blue |
| Insert color 2 EN | |
| Knob color EN | Green |
| Knob plate color EN | Green |
| Additional information | Tamper-proof |
| Height to nozzle (mm) | 219 |
| Opening mechanism | 2.5 turns head |
| Projection (mm) | 150 |
| Connection | Threaded connection M G'1 / 2 |
| Adjustable flow rate | No |
| Dual flow rate | No |
| Minimum pressure | 1 bar |
| Recommended pressure | 3 bar |
| Maximum pressure | 5 bar |
| Blocking temperature | No |
| Lenght of threaded rod (mm) | 102 |
| Max tightening | 65 |
| Packing | 1 |