




## **TECHNICAL DATASHEET**

## **LABORATORY TAPWARE**

### Candlestick type table top tap with fixed spout - 76033







#### Benefits of the product

Coating: black Rilsan

#### **Description**

Single candlestick deck-mount tap with smooth fixed spout, for drinking water. Thread connection M G'1/2, Ø 10mm removable serrated tip, 200mm projection. Polypropylene brace and flanged washer according to colour codes of the European standard NF EN 13792. Maximum tightening 65mm. Brass body and nozzle with black Nylolac coating (stronger than simple Epoxy finish). Unique and patented reinforced mounting kit, the serrated tips are designed for a steel claw washer thereby preventing rotation of the tapware. 5 year warranty. First Labo brand single deck-mount candlestick tap with smooth fixed spout REF: 76033 or approved equivalent.





# **TECHNICAL DATASHEET**

#### **Additional Information**

Product reference	76033
Previous reference	H9136PT
Brand	FirstLabo
Warranty	5 years against manufacturing defect
Special feature 1	Candlestick
Special feature 2	Tabletop
Special feature 3	Fixed spout
Nozzle 1	Removable connector Ø10 mm
Base color EN	Green
Base washer color EN	Blue
Insert color EN	Blue
Knob color EN	Green
Knob plate color EN	Green
Height to nozzle (mm)	219
Opening mechanism	2.5 turns head
Projection (mm)	200
Connection	Threaded connection M G'1 / 2Threaded connection M G'1 / 2
Adjustable flow rate	No
Dual flow rate	No
Minimum pressure	1 bar
Recommended pressure	3 bar
Maximum pressure	5 bar
Blocking temperature	No
Lenght of threaded rod (mm)	102
Max tightening	65
Packing	1