




## **TECHNICAL DATASHEET**

# LABORATORY TAPWARE

### Candlestick type table top twin tap with fixed spout - 76040







#### **Description**

Dual candlestick deck-mount tap with smooth fixed spout, National Education approved, for drinking water. Threaded connection M G'1 / 2, fixed serrated tip Ø 6mm and removable serrated tip Ø 10mm, 250mm projection. Polypropylene brace and flanged washer according to colour codes of the European standard NF EN 13792. Maximum tightening 65mm. Brass body and nozzle with black Nylolac coating (stronger than simple Epoxy finish). Unique and patented reinforced mounting kit, the serrated tips are designed for a steel claw washer thereby preventing rotation of the tapware. 5 year warranty. First Labo brand double deck-mount candlestick tap with smooth fixed spout REF: 76040 (formerly H9637PT) or approved equivalent.





# **TECHNICAL DATASHEET**

#### **Additional Information**

Product reference	76040
Previous reference	H9637PT
Brand	FirstLabo
Warranty	5 years against manufacturing defect
Special feature 1	Candlestick
Special feature 2	Tabletop
Special feature 3	Fixed spout
Nozzle 1	Fixed connector Ø6 mm
Nozzle 2	Removable connector Ø10 mm
Base washer color EN	Blue
Insert color EN	Blue
Knob color EN	Green
Knob plate color EN	Green
Height to nozzle (mm)	219
Opening mechanism	2.5 turns head
Projection (mm)	250
Connection	Threaded connection M G'1 / 2
Adjustable flow rate	No
Dual flow rate	No
Minimum pressure	1 bar
Recommended pressure	3 bar
Maximum pressure	5 bar
Blocking temperature	No
Lenght of threaded rod (mm)	102
Max tightening	65
Packing	1