



TECHNICAL DATASHEET


LABORATORY TAPWARE

Table top tap for cement bench - 76161



Description

Single tap for cement bench, for compressed air Guided water proof valve head NF, \emptyset 6mm removable serrated tip, threaded connection M G'1 / 2, 102mm projection. Polypropylene brace, base and flanged washer according to colour codes of the European standard NF EN 13792. Maximum tightening 100mm. Brass body and nozzle with black Nylolac coating (stronger than simple Epoxy finish). Unique and patented reinforced mounting kit, the serrated tips are designed for a steel claw washer thereby preventing rotation of the tapware. 5 year warranty. First Labo brand single tap for cement bench REF: 76161 (formerly H7627PT) or approved equivalent.









TECHNICAL DATASHEET

Additional Information

| Product reference | 76161 |
|-----------------------------|--------------------------------------|
| Previous reference | H7627PT |
| Brand | FirstLabo |
| Warranty | 5 years against manufacturing defect |
| Special feature 1 | Direct control tapware |
| Special feature 2 | Tabletop |
| Special feature 3 | With one tap |
| Nozzle 1 | Removable connector Ø6 mm |
| Base color EN | Blue |
| Base washer color EN | Yellow |
| Insert color EN | Yellow |
| Knob color EN | Blue |
| Knob plate color EN | Blue |
| Opening mechanism | 2.5 turns head |
| Projection (mm) | 102 |
| Connection | Threaded connection M G'1 / 2 |
| Adjustable flow rate | No |
| Dual flow rate | No |
| Minimum pressure | 1 bar |
| Recommended pressure | 5 bar |
| Maximum pressure | 7 bar |
| Blocking temperature | No |
| Lenght of threaded rod (mm) | 102 |
| Max tightening | 100 |
| Packing | 1 |