



TECHNICAL DATASHEET


LABORATORY TAPWARE

Manifold on base with two safety taps on backrest - 76187



Description

Bare manifold with two safety taps for backsplash-mount, for flammable gasses. 1/4 turn ball valve, ø 12mm fixed serrated tip, thread connection M G'1 / 2, 100mm projection. Polypropylene knob, base and flanged washer according to colour codes of the European standard NF EN 13792. Maximum tightening 55mm. Brass body and nozzle with black Nylolac coating (stronger than simple Epoxy finish). Unique and patented reinforced mounting kit, the serrated tips are designed for a steel claw washer thereby preventing rotation of the tapware. 5 year warranty. First Labo brand bare manifold with two safety taps for backsplash-mount, for flammable gasses. REF: 76187 (formerly H9446PT) or approved equivalent.









Additional Information

Product reference	76187
Previous reference	H9446PT
Brand	FirstLabo
Warranty	5 years against manufacturing defects
Special feature 1	Direct control tapware
Special feature 2	Backsplash
Special feature 3	With two taps
Nozzle 1	ixed connector Ø6 mm
Base color EN	Yellow
Base washer color EN	Yellow
Insert color EN	Yellow
Knob color EN	Yellow
Knob plate color EN	Yellow
Opening mechanism	1/4 turn head of security
Projection (mm)	100
Connection	Threaded connection M G'1 / 2
Adjustable flow rate	No
Dual flow rate	No
Minimum pressure	27 mbars
Recommended pressure	300 mbar
Maximum pressure	500 mbar
Blocking temperature	No
Lenght of threaded rod (mm)	102
Max tightening	55
Packing	1