

# TECHNICAL DATASHEET

### LABORATORY TAPWARE

### Ø 6 mm bench top or backplate outlet - 76190



#### Description

Deck-mount or backsplash nozzle, for flammable gasses. Fixed ø 6mm serrated nozzle. Thread connection M G'1/2, projection 60mm. Base and flanged washer according to colour codes of the European standard NF EN 13792. Maximum tightening 55mm. Brass nozzle with black Nylolac coating (stronger than simple Epoxy finish). Unique and patented reinforced mounting kit, the serrated tips are designed for a steel claw washer thereby preventing rotation of the tapware. 5 year warranty. First labo brand deck-mount or backsplash nozzle REF: 76190 (formerly H9419PT) or approved equivalent.







## **TECHNICAL DATASHEET**

#### **Additional Information**

| Product reference           | 76190   |
|-----------------------------|---|
| Previous reference          | H9419PT   |
| Brand                       | FirstLabo   |
| Warranty                    | 5 years against manufacturing defects             |
| Special feature 1           | Remotely controlled tapware/ laboratory fume hood |
| Special feature 2           | Tabletop or backsplash                            |
| Nozzle 1                    | ixed connector Ø6 mm                              |
| Base color EN               | Yellow  |
| Base washer color EN        | Yellow  |
| Projection (mm)             | 60  |
| Connection                  | Threaded connection M G'1 / 2                     |
| Adjustable flow rate        | No  |
| Dual flow rate              | No  |
| Minimum pressure            | 27 mbars  |
| Recommended pressure        | 300 mbar  |
| Maximum pressure            | 500 mbar  |
| Blocking temperature        | No  |
| Lenght of threaded rod (mm) | 102   |
| Max tightening              | 55  |
| Packing                     | 1   |