



### LABORATORY TAPWARE

#### Table column, projection 150 mm, with fixed and swivel spout, with fixed nozzle - 76799





#### Benefits of the product

- Smooth interior spout, fixed and swivel (at the choice of the technician, using a blocking screw)
- The shape of the base ensures a better sealing of the washbasin
- White colour body: purity and hygiene
- Nice and modern spout bending
- Thickness of the spout: 20 mm diameter for all the spout
- Resistance to corrosion and impact: RILSAN coating
- Smooth surface, limits deposits

#### Description

Deck-mounted column with smooth fixed and swivel (at the choice of the technician, using a screw) removable spout, for drinking water. Thread connection M G'1/2,  $\varnothing$  6mm fixed nozzle, 150mm projection. Maximum tightening 50mm. Body and nozzle in brass according to colour codes of the European standard NF EN 13792. Brass body and nozzle with white Nylolac coating (stronger than simple Epoxy finish). Unique and patented reinforced mounting kit, the serrated tips are designed for a steel claw washer thereby preventing rotation of the tapware. 5 year warranty. First Labo brand deck-mounted column smooth fixed and swivel removable spout REF: 76799 or approved equivalent





## TECHNICAL DATASHEET

### Additional Information

<b>Product reference</b>	76799
<b>Previous reference</b>	NC
<b>Brand</b>	FirstLabo
<b>Warranty</b>	5 years against manufacturing defect
<b>Special feature 1</b>	Fixed spout
<b>Special feature 2</b>	Swivel spout
<b>Special feature 3</b>	Tabletop
<b>Nozzle 1</b>	Fixed connector Ø6 mm
<b>Additional information</b>	Possibility to install the column on a fume cupboard
<b>Height to nozzle (mm)</b>	147
<b>Projection (mm)</b>	150
<b>Connection</b>	M G'1/2 threaded rod
<b>Adjustable flow rate</b>	No
<b>Dual flow rate</b>	No
<b>Minimum pressure</b>	1 bar
<b>Recommended pressure</b>	3 bar
<b>Maximum pressure</b>	5 bar
<b>Blocking temperature</b>	No
<b>Length of threaded rod (mm)</b>	102
<b>Max tightening</b>	50
<b>Packing</b>	1