
# **TECHNICAL DATA SHEET**



Range: PRESTO CHEF - Professionnal Kitchen range **Ref:** 70800 - Deck-mounted mixer – upward spout





#### > THE PRODUCT BENEFITS

- · Resistant to intensive use
- Reinforced body / spout interface with double sliding bearings: no play and high endurance
  Robust spout: 22 mm in diameter
  Ergonomic and robust control: easy grip
  Robust mixing handle possibility to install it laterally (installation flexibility)

- Hygiene: spout with smooth interior Product design

- Ease of cleaning
  High spout to let large containers pass
  Ease of maintenance: availability of all spare parts
  Flow straightener to channel water and avoid lateral water splashes

# > TECHNICAL SPECIFICATIONS

# > Model:

- Single-lever deck-mounted mixer with spout above
   360 ° swivel spout, 250 mm projection, height under spout 276 mm, diameter 22 mm. Spout thickness: 1.5 mm.
- Ceramic cartridge Interchangeable anti-tartar flow straightener

#### > Recommended working pressure:

1 to 5 bars

#### > Flow rate:

• 25L / min at 38°C at 3 bar

#### > Hydraulic supply:

• G 1/2 " (15x 21)

#### > Material and color of finish:

- Chromed brass body and spoutMaterial compliant with the "UBA" list

## > Thermal resistance :

• Withstands a temperature of 75 ° C for 30 minutes (as part of thermal shock).

### > Delivered with:

- 1 fixing bracket
  2 PEX flexible hoses with stainless steel braided nut G1 / 2 " Lg 660 mm with non-return valves NF
  2 filters

• Possibility of adding an extension sold separately, facilitating the passage of large containers

### > Standards and approvals:

- Chromed brass body compliant with standards NF EN1982 / NF EN 12164 / NF EN 12165
   Nickel-Chrome surface treatment according to NF EN12540
   Resistance to neutral salt spray (NSS): 200 h according to NF ISO 9227











