# **TECHNICAL DATA SHEET**




sanifirst

Range: Sanifirst - Healthcare taps

Ref: 75617 - Single hole washbasin mixer tap - Energy savings -without drainage





#### > Benefits of the product

- Opening on cold water: avoids drawing hot water when first turned on (energy savings)
- Spout height and projection adapted to washing at the washbasin Perfectly adapted to all bathrooms.
- Flow between 4 and 6L / min at 3 bar in accordance with the French norm standard "Medical"; possible flow modification, in case of disassembly of the limiters, by adjusting screw between 4 and 20L / min.
  Water savings and controlled water consumption

#### > Model

- Height under spout: 92 mm.
- Projection: 100 mm.Height of the control: 150 mm.

- Without waste, deck-mounted.
  Star-shaped flow straightener M24 x1.
  Energy-saving 35 mm diameter ceramic cartridge with temperature limit limiter, allowing 9-position adjustment.

# > Flow rate

• between 4 and 6L / min at 3 bar - in accordance with the NF "Medical environment" standard; modification of the flow rate possible, if the limiters are removed, by adjusting screw between 4 and 20L / min.

### > Recommended pressure

- 3 bar avoid pressure differences greater than 1 bar between DHW and DCW. Minimum pressure: 1 bar.
- Maximum pressure: 5 bar.

### > Materials

· Chromed brass.

## > Connection

• Hoses with 10X1 stainless steel braided SPEX sheath, EP G'3 / 8. Lg 500 mm with basket filter gaskets and flow limiter.



