




Range: Sanifirst - Healthcare taps

Ref: 75112 - Hospital thermostatic shower mixer, thermal shock - Mastermix



> Benefits of the product

- **MASTERMIX PATENTED TECHNOLOGY**
- **No cross-connection between hot and cold water**
- **No check valve needed**
- **Cold body: safety insulation**
- **Temperature and flow controls easily identifiable**
- **Temperature maintenance and anti-scalding safety**
- **Quick and easy maintenance**
- **Secure thermal shock: accessible only by authorized persons**
- **Adapted to people with reduced mobility (elderly people, children ...)**

> Anti-scalding safety

- Temperature knob with temperature limiter at 38 ° C. Unlocking secured for thermal shock and accessible only by technical services without removing the knob.

> Anti-bacterial proliferation safety

- Unique DCW AND DHW anti-intercommunication system, produced by the association of a specific ceramic cartridge and a thermostatic cartridge conforming to NF EN 1111.

> Flow rate

- Adjustable between 5 and 14L / min at 3 bar.

> Recommended pressure

- 3 bar - avoid pressure differences greater than 1 bar between DHW and DCW.
- Minimum pressure: 1 bar.
- Maximum pressure: 5 bar.

> Materials

- Chromed brass.

> Connection

- captive nut G'3 / 4 supplied with rosettes and eccentric fittings M G'1 / 2 - M G'3 / 4.

> Warranty

- 10 years against any manufacturing defect.
- 3 years for the thermostatic cartridge.