


Range: PRESTO LINEA®

Ref: 57102CB - Wall-mounted single sensor tap, all-integrated, battery, 1,9l/min, brushed copper



> Working pressure :

- 1 to 5 bar

> Function:

- Starts and stops automatically by hand detection
- Sensor trigger suitable for PRIM, elderly, children and disabled people

> Flow:

- 1.9l/min at 3 bar with integrated regulated flow spray

> Hydraulic supply :

- G 1/2" (15x21) - Cold or premixed water
- Integrated stop valve

> Power supply :

- Integrated 3V CR123A lithium batteries (x2)

> Material and colour finish:

- External brass body: brushed copper finish (PVD treatment)
- Molded metal cover: brushed copper finish (PVD treatment)
- Internal lead-free brass body

> Thermal resistance :

- Resistant to a temperature of 75°C for 30-minute-thermal-shocks

> Security :

- Anti-overflow security time set to 30 seconds preventing the water to flow continuously
- Automatic shutdown of solenoid valve in case of low battery or sensor damage
- Duty flush 30 sec every 24h after last use (adjustable flow time and frequency with PRESTOCOM toolkit: <https://www.presto.fr/apropos/prestocom>)
- Smooth inner body for limiting biofilm binding and bacterial development
- Low battery alert (blinking led light)

> Installation:

- Recommended installation hight : 30 cm above the bottom of the washbasin

> Delivered with

- 1 wall rose
- 1 Filter gasket
- 1 Self-adhesive sticker
- 1 Instruction manual

> Standards & approvals :

- Lead-free brass in accordance with NF EN1982, EN12164, NF EN 12165, 4MS, RoHS, Reach, NSF-372, UBA list compliant
- Dezincification compliant with ISO 6509 and NDZ
- 200-hour neutral salt spray resistant (NSS) in accordance with NF ISO 9227