



**Range:** PRESTO LINEA®

**Ref:** 57200NP - Deck-mounted sensor single tap for washbasin, mains 230V, 3l/min with stop valve Polished Black



#### > Working pressure

- 1 to 5 bar

#### > Function

- Starts and stops automatically by hand detection
- Sensor trigger suitable for PRM, elderly, children and disabled people

#### > Flow

- 3l/min at 3 bar with integrated regulated anti-limescale aerator

#### > Hydraulic supply

- F G 3/8" (12x17) hose

#### > Power supply

- Mains-operated with 230 V AC / 7 V DC transformer in IP65 waterproof case

#### > Materials and Finish:

- Brass body with smooth inside body, Polished Black Finish
- Molded metal cover, Polished Black Finish

#### > Thermal resistance

- Resistant to a temperature of 75°C for 30-minute-thermal-shocks

#### > Security

- Anti-overflow security time set to 30 seconds preventing the water to flow continuously
- Automatic shutdown of solenoid valve in case of power failure or sensor damage
- Duty flush 30 sec every 24h after last use (adjustable flow time and frequency)
- Low battery alert (blinking led light)

#### > Installation

- Recommended installation : 30 cm minimum between the sensor and the basin

#### > Delivered with

- 1 Brass clamping nut, 1 Gasket and 1 Washer
- 1 PEX hose with revolving nut and filter gasket
- 1 M M G 3/8" (12x17) stop valve
- 1 Self-adhesive sticker
- 1 Instruction manual

#### > Standards & approvals

- Brass body in accordance with NF EN1982, EN12164, NF EN 12165,
- UBA list compliant
- 200-hour neutral salt spray resistant (NSS) in accordance with NF ISO 9227

