




TECHNICAL DATASHEET

HEALTHCARE TAPWARE

Thermostatic shower mixer, special thermal shock, with hydrotherapy kit - 75108





Benefits of the product

- Ergonomic lever handle: easy grip
- Smooth interior removable spout: easy cleaning and disinfection, limits the formation of biofilm

Multifunction ceramic cartridge \varnothing 35: 7-setting temperature limit stop, flow settings from 2I to 13.8I/min.

- Star shaped flow straightener: Limits the water spray, no water retention.

Description

150mm span thermostatic wall-mount shower mixer Dual flow control knob and a special heat shock knob locked at 38 °C with a secure release system for thermal shock without changing knob and accessible only by technical services. Hot and cold water supplies equipped with back-flow valves, shower outlet M'1 / 2. ½ turn ceramic head for flow control and NF Thermostatic cartridge for adjusting the temperature. Body and knobs in polished chrome-plated brass. Supplied with off-centre fittings M1 / 2 with chrome rosette cover plates and filter seals; 2-spray shower; metal plastic hose L 0.85m; 25 mm diameter bar L 600 mm and soap holder. 3-year warranty for the thermostatic cartridge and 10 years for the rest of the fittings. Sanifirst brand thermostatic shower mixer, 150mm span, REF: 75108 or approved equivalent.





TECHNICAL DATASHEET

Additional Information

Product reference	75108
Previous reference	FL3730CT KIT
Brand	Sanifirst
Warranty	10 years against manufacturing defects / 3 years for the thermostatic cartridge
Special feature 1	1/2 turn ceramic head
Special feature 2	Shower
Clip-on spout	No
Connection	LN G'3 / 4 comes with rosettes and off-centre fittings M G'1 / 2 - M G'3 / 4
Minimum pressure	1 bar
Recommended pressure	3 bar - avoid pressure differences of more than 1 bar between the hot and cold water supplies
Maximum pressure	5 bar
Cartridge	Thermostatic
Coating	Nickel > 10 microns - Chrome > 0.3 microns