


**Range:** Sanifirst - Healthcare taps

**Ref:** 75700 - MASTERMIX Thermostatic shower mixer - Wall-mounted downward outlet



## > Benefits of the product

- Certified NF medical classification E.C.A.U.M: E0 Ch2 A1 U3
- MASTERMIX PATENTED TECHNOLOGY
- Ingenious combination of specific ceramic cartridge and thermostatic cartridge: safety and reliability.
- No cross-connection between hot water and cold water.
- Without check-valves
- Cold body: anti-scalding insulation
- Body with smooth interior: limits the risk of bacterial proliferation (legionella, pseudomonas...)
- Dual safety temperature limiter (38°C and 41°C) and adjustment of maximum flow limiter
- Temperature stability and anti-scalding safety
- Quick and easy installation and maintenance.
- Safe thermal shock: only accessible by technical staff
- Excentric connectors with 1/4 turn stop valves included
- Body docking with the wall: optimized cleaning of all contact surfaces

## > Anti-scalding safety

- Temperature knob with double temperature limiter 38 ° C and 41 ° C. Unlocking secured for thermal shock and accessible only by technical services without removing the knob.

## > Anti-bacterial proliferation safety

- Unique and patented DCW and DHW anti-intercommunication system, allowing the removal of the non-return valves on the DCW and DHW inlets of the mixing valve, produced by a ceramic cartridge and a thermostatic cartridge conforming to NF EN 1111

## > Model

- MASTERMIX thermostatic shower mixer without pressurized mixing chamber (avoiding DCW and DHW intercommunication upstream of the shutter).
- Certified NF medical classification (NF 077-15)
- Adjustable temperature from 18 to 41 ° C

## > Flow rate

- Maximum flow rate adjustable to 6 - 9 - 12 L /min by the manager

## > Recommended pressure

- 3 bar - avoid pressure differences greater than 1 bar between DHW and DCW.
- Minimum pressure: 1 bar.
- Maximum pressure: 5 bar.

## > Material

- Rotating ergonomic body and knobs in chrome-plated zamak

## > Connection

- Exclusively using a fixing plate with M G'1 / 2 connection 150 +/- 10mm center distance integrating stop valves, filtration and acoustic connection (supplied)
- Shower outlet M'1 / 2 downwards with integrated check valve

## > Warranty

- 10 years against any manufacturing defect.
- 3 years for the thermostatic cartridge.