



LABORATORY TAPWARE

Gooseneck bare downwards swivel spout - 76011



Benefits of the product

Coating: black Rilsan

Description

Gooseneck under-shelf downward drinking water tap with swivel removable smooth spout for backsplash. Water tight guided valve head NF, threaded connection M G'1 / 2, \varnothing 10 mm removable serrated tip, 250mm projection. Polypropylene brace according to colour codes of the European standard NF EN 13792. Maximum tightening 55mm. Brass body and nozzle with black Nylolac coating (stronger than simple Epoxy finish). 5 year warranty. First Labo brand downward gooseneck tap with swivel smooth removable spout for backsplash REF: 76011 or approved equivalent.



TECHNICAL DATASHEET

Additional Information

| | |
|------------------------------------|--------------------------------------|
| Product reference | 76011 |
| Previous reference | H9645PT |
| Brand | FirstLabo |
| Warranty | 5 years against manufacturing defect |
| Special feature 1 | Direct control tapware |
| Special feature 2 | Backsplash |
| Special feature 3 | Swivel spout |
| Nozzle 1 | Removable connector Ø10 mm |
| Insert color EN | Blue |
| Knob color EN | Green |
| Knob plate color EN | Green |
| Height to nozzle (mm) | 150 |
| Length of spout (mm) | 200 |
| Opening mechanism | 2.5 turns head |
| Projection (mm) | 250 |
| Connection | Threaded connection M G'1 / 2 |
| Adjustable flow rate | No |
| Dual flow rate | No |
| Minimum pressure | 1 bar |
| Recommended pressure | 3 bar |
| Maximum pressure | 5 bar |
| Blocking temperature | No |
| Length of threaded rod (mm) | 102 |
| Max tightening | 55 |
| Packing | 1 |