



### LABORATORY TAPWARE

Ø 6 mm outlet for cement bench - 76015



#### Benefits of the product

Coating: black Rilsan

#### Description

Drinking water deck-mount nozzle. Thread connection M G'1/2, ø 6mm fixed spout. Polypropylene brace, base and flanged washer according to colour codes of the European standard NF EN 13792. Maximum tightening 100mm. Brass nozzle with black Nylolac coating (stronger than simple Epoxy finish). Brass body and nozzle with black Nylolac coating (stronger than simple Epoxy finish). Unique and patented reinforced mounting kit, the serrated tips are designed for a steel claw washer thereby preventing rotation of the tapware. 5 year warranty. First Labo brand deck-mount nozzle REF: 76015 or approved equivalent.





## TECHNICAL DATASHEET

### Additional Information

<b>Product reference</b>	76015
<b>Previous reference</b>	H9018PT
<b>Brand</b>	FirstLabo
<b>Warranty</b>	5 years against manufacturing defect
<b>Special feature 1</b>	Remotely controlled tapware/ laboratory fume hood
<b>Special feature 2</b>	Tabletop
<b>Nozzle 1</b>	Fixed connector Ø6 mm
<b>Base color EN</b>	Green
<b>Base washer color EN</b>	Blue
<b>Insert color EN</b>	Blue
<b>Additional information</b>	Installation possible for fume cabinet
<b>Height to nozzle (mm)</b>	60
<b>Projection (mm)</b>	54
<b>Connection</b>	Threaded connection M G'1 / 2
<b>Adjustable flow rate</b>	No
<b>Dual flow rate</b>	No
<b>Minimum pressure</b>	1 bar
<b>Recommended pressure</b>	3 bar
<b>Maximum pressure</b>	5 bar
<b>Blocking temperature</b>	No
<b>Length of threaded rod (mm)</b>	152
<b>Max tightening</b>	100
<b>Packing</b>	1