



TECHNICAL DATASHEET

LABORATORY TAPWARE

Ø 6 mm bench top or backplate outlet - 76016



Benefits of the product

Coating: black Rilsan

Description

Drinking water deck-mount nozzle. Thread connection M G'1/2, Ø 6mm fixed spout. Polypropylene brace, base and flanged washer according to colour codes of the European standard NF EN 13792. Maximum tightening 55mm. Brass nozzle with black Nylolac coating (stronger than simple Epoxy finish). Unique and patented reinforced mounting kit, the serrated tips are designed for a steel claw washer thereby preventing rotation of the tapware. 5 year warranty. First Labo brand deck-mount nozzle REF: 76016 or approved equivalent.



TECHNICAL DATASHEET

Additional Information

Product reference	76016
Previous reference	H9019PT
Brand	FirstLabo
Warranty	5 years against manufacturing defect
Special feature 1	Remotely controlled tapware/ laboratory fume hood
Special feature 2	Tabletop or backsplash
Nozzle 1	Fixed connector Ø6 mm
Base color EN	Green
Base washer color EN	Blue
Additional information	Installation possible for fume cabinet
Height to nozzle (mm)	60
Projection (mm)	54
Connection	Threaded connection M G'1 / 2
Adjustable flow rate	No
Dual flow rate	No
Minimum pressure	1 bar
Recommended pressure	3 bar
Maximum pressure	5 bar
Blocking temperature	No
Lenght of threaded rod (mm)	102
Max tightening	55
Packing	1