




LABORATORY TAPWARE

Table top dual taps at 180° - 76164



Description

Dual tap socket at 180° for bench, for compressed air Guided water proof valve head NF, removable serrated tip \varnothing 6mm, thread connection M G'1 / 2, 120mm projection. Polypropylene brace, base and flanged washer according to colour codes of the European standard NF EN 13792. Maximum tightening 55mm. Brass body and nozzle with black Nylolac coating (stronger than simple Epoxy finish). Unique and patented reinforced mounting kit, the serrated tips are designed for a steel claw washer thereby preventing rotation of the tapware. 5 year warranty. First Labo brand dual tap at 180° for bench REF: 76164 (formerly H7630PT) or approved equivalent.





TECHNICAL DATASHEET

Additional Information

| | |
|------------------------------------|--------------------------------------|
| Product reference | 76164 |
| Previous reference | H7630PT |
| Brand | FirstLabo |
| Warranty | 5 years against manufacturing defect |
| Special feature 1 | Direct control tapware |
| Special feature 2 | Tabletop |
| Special feature 3 | With two taps |
| Nozzle 1 | Removable connector Ø6 mm |
| Base color EN | Blue |
| Base washer color EN | Yellow |
| Insert color EN | Yellow |
| Knob color EN | Blue |
| Knob plate color EN | Blue |
| Opening mechanism | 2.5 turns head |
| Projection (mm) | 120 |
| Connection | Threaded connection M G'1 / 2 |
| Adjustable flow rate | No |
| Dual flow rate | No |
| Minimum pressure | 1 bar |
| Recommended pressure | 5 bar |
| Maximum pressure | 7 bar |
| Blocking temperature | No |
| Length of threaded rod (mm) | 102 |
| Max tightening | 55 |
| Packing | 1 |