



LABORATORY TAPWARE

Connector with two 90° taps - 76202



Description

Connector with two 90° safety taps for Educational establishments, for combustible gases. 1/4 Turn ball valve heads, M G'1/2 outlet, threaded M 'G1/2 connector, 51mm projection. Polypropylene knobs and base washer using the NF EN 13792 European standard colour codes. Maximum tightening 65mm. Brass body and tips with black Nylolac coating (stronger than a basic epoxy finish) Single patented fixture kit, our grooved stems are designed to be fitted with a steel claw washer that prevents the tapware from any rotation. 5 year guarantee. First Labo brand type double 90° safety tap unit REF: 76202 or approved equivalent..



TECHNICAL DATASHEET

Additional Information

Product reference	76202
Previous reference	H9429PT38
Brand	FirstLabo
Warranty	5 years against manufacturing defects
Special feature 1	Direct control tapware/ National Education
Special feature 2	Tabletop
Special feature 3	With two taps
Nozzle 1	M G'1/2
Base color EN	Yellow
Base washer color EN	Yellow
Insert color EN	Yellow
Knob color EN	Yellow
Knob plate color EN	Yellow
Additional information	Tamper-proof
Opening mechanism	1/4 turn head of security
Projection (mm)	75
Connection	Threaded connection M G'1 / 2
Adjustable flow rate	No
Dual flow rate	No
Minimum pressure	27 mbars
Recommended pressure	300 mbar
Maximum pressure	500 mbar
Blocking temperature	No
Lenght of threaded rod (mm)	102
Max tightening	55
Packing	1